UL Product iQ™

QMFZ2.E249605 - Plastics - Component

Plastics - Component

SUZHOU OMAY OPTICAL MATERIALS CO LTD E249605
158-30 HUASHAN RD
SND
SUZHOU, JIANGSU 215011 China

Dsg	Color	Min Thk mm	Flame Class	HWI	HAI	RTI Elec Str	RTI Mech Imp Str		HVTR	D495	CTI
Polycarbonate (PC) furnished as film or sheet											
V11, V42, V32, V41, V21, V31, V61, V71, V11-P, V42-P, V31-P, V32-P, V41-P, V21-P, V61-P, V71-P											
	NC	0.20-0.22	VTM-0	-	-	80	80	80	-	-	-
V11B , V42B, V32B, V41B,V21B, V31B, V61B, V71B, V11B-P, V42B-P, V31B-P, V32B-P, V41B-P, V21B-P, V61B-P, V71B-P											
	BK	0.1	VTM-2	-	-	80	80	80	-	-	-
		0.25	VTM-0	-	-	80	80	80	-	-	-
Polycarbonate (PC) furnished as sheets											
G11,G11W, G11B, SB11, SG11, FG11, G11-R, G11-BU, G11W, FG(a), LSC(a), EHF(a),OMR(a)-UV, C71-A, C71-B, C71-C, ST(a), OM(a)-UV,G(a)W,G11B, IMD11, LCD11, LCD41, LCD61, LCD11B, T11, UV11, SR11, LC11, LC21, LC32, LC42, LC21B, LC11B, LC32B, LC21W, LC32W, LC42B, LC42W											
	NC	0.121	V-2	-	-	80	80	80	-	-	-
		1.0-1.1	V-2	-	-	80	80	80	-	-	-
G42, G51, G42F, G21F, G32, G32F, G52, G21, G41, G41F, G21B, G42B, G61, G71, IMD42, IMD41, LD21, LD21W, LD32, LD42, LD42W, LD52W, LD41W, LD21W-F, LD42W-F, T41, T32F, SR42, SR41, SR21											
	NC	0.120-0.132	VTM-2	-	-	80	80	80	-	-	-
		0.5-0.55	V-2	-	-	80	80	80	-	-	-
OM(a), BLC(a)(b), GAP(a)	NC	0.075	VTM-2	-	-	80	80	80	-	-	-
		0.125	VTM-2	-	-	80	80	80	-	-	-
		0.5	V-2	-	-	80	80	80	-	-	-
		0.8	V-2	-	-	80	80	80	-	-	-
		3.0	V-2	-	-	80	80	80	-	-	-
OMF(a), BLC(a)(b)F, RHA(a)	NC	0.8	V-0	-	-	80	80	80	-	-	-
		3.0	V-0	-	-	80	80	80	-	-	-

U(a), U(a)-P	NC	0.110-0.250	VTM-0	-	-	80	80	80	-	-	-
		0.370-0.8	V-0	-	-	80	80	80	-	-	-
U(a)B, U(a)B-P	BK	0.110-0.250	VTM-0	-	-	80	80	80	-	-	-
		0.370-0.8	V-0	-	-	80	80	80	-	-	-
Polycarbonate (PC) furnished as sheets or rolls											
G11-N	NC	0.175-0.19	V-2	-	-	80	80	80	-	-	-
SE11, SE21, SE41, SE42, SE31, SE61, SE71, SE32, SE52, SE51, SE62, SE72											
	NC	0.125	V-0	0	4	80	80	80	-	-	-
		0.25	V-0	0	4	80	80	80	-	-	-
		0.8-0.88	V-0	0	0	80	80	80	-	-	-
SE42B,SE21B, SE41B, SE42W, SE42B-F, SE41B-F, SE32B, SE31B, SE61B, SE71B, SE52B, SE51B, SE62B, SE72B, SE21W, SE41W, SE32W											
	BK	0.25	V-0	0	0	80	80	80	-	-	-
		0.8-0.88	V-0	0	0	80	80	80	-	-	-
Polycarbonate (PC)/Polymethyl Methacrylate (PMMA) furnished as film or sheets											
GMC	NC	0.5	HB	-	-	50	50	50	-	-	-
		2.0	HB	-	-	50	50	50	-	-	-
Polycarbonate/Polybutylene Terephthalate (PC/PBT) furnished as sheets or rolls											
SE900	NC	0.125-0.14	VTM-0	4	4	75	75	75	-	-	-
		0.50-0.55	V-0	4	0	75	75	75	-	-	-
Polypropylene (PP) furnished as pellets											
ESC(a)B, ESC-HF(a)B, BSC(a)B, ESC(a)B-ECO, ESC(a)B-(b)											
	BK	0.3-0.75	V-0	-	-	65	65	65	-	-	1
ESC(a)W, ESC-HF(a)W, BSC(a)W, ESC(a)W-ECO, ESC(a)W-(b)											
	WT	0.3-0.75	V-0	-	-	65	65	65	-	-	1
SC(a)B	BK	0.38 - 0.74	V-0	4	0	65	65	65	-	-	0
		0.75 - 0.9	V-0	4	0	65	65	65	-	-	-

(a) - May be followed by a two digit suffix [00-99] inclusive, indicating textures of both sides of the film/sheet

(b) - May be 001-999 representing different client designations.

Marking: Company name, material designation On container, wrapper Or finished part.

Last Updated on 2022-02-09

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明： "© 2022 UL LLC"